

View Online at <https://aerobasegroup.com/nsn/2920-00-294-3932>

Terminal Quantity:

2

Terminal Type:

Threaded stud

Furnished Items:

Cooling fan and drive pulley

Keyway Width:

0.125 inches

Mounting Hole Quantity:

3

Unthreaded Portion Length:

1.125 inches

Mounting Hole Thread Direction:

Right-hand

Mounting Style:

Bracket mtd w/three mtg holes, top hole threaded

Environmental Protection:

Corrosion resistant and fungus resistant

Keyway Length:

0.500 inches

Largest Diameter:

0.625 inches

Submersibility:

Nonsubmersible

Unpackaged Unit Length:

8.750 inches

Unpackaged Unit Width:

5.250 inches

Unpackaged Unit Height:

5.250 inches

Shaft Rotation Direction:

Clockwise

Distance From End To Keyway Center:

0.333 inches

Armature Minimum Speed In Rpm At Full Current Output:

2000

Maximum Output Current Rating In Amps:

10.0

Minimum Current Cut-in Speed In Rpm:

1850

Shaft Drive End Style:

Straight shaft end w/keyway

Distance Between Shaft Center And Bottom Mounting Hole Center:

3.875 inches

Distance Between Shaft Center And Top Mounting Hole Center:

3.625 inches

Angular Deviation Of First Hole From Top Center In Deg:

193.0

Angular Deviation Of Second Hole From First Hole In Deg:

169.0

Distance Between Inside Surfaces Of Hinge Bracket:

7.250 inches

Distance Between Outside Surfaces Of Hinge Bracket:

8.250 inches

Bottom Mounting Hole Diameter:

0.312 inches

Maximum Rated Armature Speed In Rpm:

2050

Mounting Hole Thread Series Designator:

Unc

Mounting Hole Thread Diameter:

0.250 inches

Mounting Hole Thready Qty Per Inch (tpi):

20

Mounting Hole Thread Class:

1b

Voltage In Volts:

24.0

Special Features:

External blast cooling

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A14700