

View Online at <https://aerobasegroup.com/nsn/2920-00-314-0556>

Keyway Width:

0.250 inches

Mounting Hole Thread Direction:

Right-hand

Mounting Style:

Bracket mtd w/three mtg holes, top hole threaded

Environmental Protection:

Corrosion resistant

Keyway Length:

1.000 inches

Submersibility:

Submersible

Shaft Rotation Direction:

Clockwise

Ground Polarity Type:

Negative

Armature Minimum Speed In Rpm At Full Current Output:

1650

Maximum Output Current Rating In Amps:

100.0

Minimum Current Cut-in Speed In Rpm:

1600

Rectifier Location:

Integral

Grounding Method:

Internal

Shaft Drive End Style:

Straight shaft end w/keyway

Distance Between Shaft Center And Bottom Mounting Hole Center:

4.125 inches

Distance Between Shaft Center And Top Mounting Hole Center:

3.851 inches

Angular Deviation Of First Hole From Top Center In Deg:

21.0

Angular Deviation Of Second Hole From First Hole In Deg:

159.0

Bottom Mounting Hole Diameter:

1.125 inches

Maximum Rated Armature Speed In Rpm:

8000

Mounting Hole Thread Series Designator:

Unc

Mounting Hole Thread Diameter:

0.375 inches

Mounting Hole Thready Qty Per Inch (tpi):

16

Mounting Hole Thread Class:

2b

Voltage In Volts:

28.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A14700