

View Online at <https://aerobasegroup.com/nsn/2920-00-333-5003>

**Body Material:**

Steel

**Drive Connection Type:**

Coupling half

**Environmental Protection:**

Fungus resistant

**Performance Type:**

Low tension

**Shaft Rotation Direction:**

Clockwise

**Mounting Facility Quantity:**

4

**Pole Quantity:**

1

**Distributor Cap:**

Included

**Mounting Method:**

Flange

**Impulse Quantity Per Revolution:**

6

**Ignition Type For Which Designed:**

Single

**Secondary Terminal Type:**

Threaded

**Spark Plug Terminal Accommodation Thread Series:**

Unef

**Spark Advance Control Method:**

Manual

**Maximum Advance Deg:**

15.0

**Rotation Element Type:**

Wound armature

**Contact Set Quantity:**

1

**Rpm At Maximum Advance:**

450.0

**Mounting Facility:**

Threaded hole

**Features Provided:**

Radio interference shielding

**Spark Distribution Method:**

Gap

**Spark Plug Terminal Accommodation Thread Diameter:**

0.688 inches

**Spark Plug Terminal Accommodation Thread Qty Per Inch (tpi):**

24

**Surface Treatment:**

Enamel

**Surface Treatment:**

Enamel

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A12200