NSN 2920-00-333-5003

Ignition Magneto - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2920-00-333-5003

| Dody Material | | | |
|--------------------|---------------------------------|-----|--|
| Body Material: | | | |
| Steel | T | | |
| Drive Connectio | і туре: | | |
| Coupling half | | | |
| Environmental F | rotection: | | |
| Fungus resistant | | | |
| Performance Ty | e: | | |
| Low tension | | | |
| Shaft Rotation D | rection: | | |
| Clockwise | | | |
| Mounting Facilit | Quantity: | | |
| 4 | | | |
| Pole Quantity: | | | |
| 1 | | | |
| Distributor Cap: | | | |
| Included | | | |
| Mounting Metho | 1: | | |
| Flange | | | |
| Impulse Quantit | Per Revolution: | | |
| 6 | | | |
| Ignition Type Fo | Which Designed: | | |
| Single | | | |
| Secondary Term | nal Type: | | |
| Threaded | | | |
| Spark Plug Tern | inal Accommodation Thread Serie | es: | |
| Unef | | | |
| Spark Advance | control Method: | | |
| Manual | | | |
| Maximum Advar | ce Deg: | | |
| 15.0 | | | |
| Rotation Elemer | : Туре: | | |
| Wound armature | | | |
| Contact Set Qua | ntity: | | |
| 1 | | | |
| Rpm At Maximu | n Advance: | | |
| 450.0 | | | |
| Mounting Facilit | : | | |
| Threaded hole | | | |
| Features Provid | d: | | |
| Radio interferenc | shielding | | |
| Spark Distribution | | | |
| Gap | | | |

NSN 2920-00-333-5003

Ignition Magneto - Page 2 of 2



Spark Plug Terminal Accommodation Thread Diameter:

0.688 inches

Spark Plug Terminal Accommodation Thready Qty Per Inch (tpi):

24

Surface Treatment:

Enamel

Surface Treatment:

Enamel

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A12200