

View Online at <https://aerobasegroup.com/nsn/2920-00-351-9606>

**Thread Direction:**

Right-hand

**Thread Length:**

0.375 inches

**Furnished Items:**

Voltage regulator

**Second Step Diameter:**

Between 0.749 inches and 0.750 inches

**Keyway Width:**

0.156 inches

**Unthreaded Portion Length:**

1.000 inches

**Mounting Hole Thread Direction:**

Right-hand

**Mounting Style:**

Bracket mtd w/three mtg holes, top hole threaded

**Keyway Length:**

0.750 inches

**Submersibility:**

Nonsubmersible

**Shaft Rotation Direction:**

Clockwise

**Distance From End To Keyway Center:**

0.750 inches

**Thread Diameter:**

0.500 inches

**Ground Polarity Type:**

Positive

**Armature Minimum Speed In Rpm At Full Current Output:**

2500

**Maximum Output Current Rating In Amps:**

13.5

**Minimum Current Cut-in Speed In Rpm:**

960

**Grounding Method:**

External

**Shaft Drive End Style:**

Straight shaft end, threaded, w/keyway

**Distance Between Shaft Center And Bottom Mounting Hole Center:**

2.094 inches

**Distance Between Shaft Center And Top Mounting Hole Center:**

2.094 inches

**Angular Deviation Of First Hole From Top Center In Deg:**

0.0

**Angular Deviation Of Second Hole From First Hole In Deg:**

180.0

**Distance Between Inside Surfaces Of Hinge Bracket:**

7.125 inches

**Distance Between Outside Surfaces Of Hinge Bracket:**

8.234 inches

**Bottom Mounting Hole Diameter:**

0.328 inches

**Maximum Rated Armature Speed In Rpm:**

8000

**Thread Series:**

Unf

**Thread Class:**

2a

**Mounting Hole Thread Series Designator:**

Unc

**Mounting Hole Thread Diameter:**

0.375 inches

**Mounting Hole Thready Qty Per Inch (tpi):**

16

**Mounting Hole Thread Class:**

2b

**Thready Qty Per Inch (tpi):**

20

**Voltage In Volts:**

6.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A14700