

View Online at <https://aerobasegroup.com/nsn/2920-00-351-9606>

Thread Direction:

Right-hand

Thread Length:

0.375 inches

Furnished Items:

Voltage regulator

Second Step Diameter:

Between 0.749 inches and 0.750 inches

Keyway Width:

0.156 inches

Unthreaded Portion Length:

1.000 inches

Mounting Hole Thread Direction:

Right-hand

Mounting Style:

Bracket mtd w/three mtg holes, top hole threaded

Keyway Length:

0.750 inches

Submersibility:

Nonsubmersible

Shaft Rotation Direction:

Clockwise

Distance From End To Keyway Center:

0.750 inches

Thread Diameter:

0.500 inches

Ground Polarity Type:

Positive

Armature Minimum Speed In Rpm At Full Current Output:

2500

Maximum Output Current Rating In Amps:

13.5

Minimum Current Cut-in Speed In Rpm:

960

Grounding Method:

External

Shaft Drive End Style:

Straight shaft end, threaded, w/keyway

Distance Between Shaft Center And Bottom Mounting Hole Center:

2.094 inches

Distance Between Shaft Center And Top Mounting Hole Center:

2.094 inches

Angular Deviation Of First Hole From Top Center In Deg:

0.0

Angular Deviation Of Second Hole From First Hole In Deg:

180.0

Distance Between Inside Surfaces Of Hinge Bracket:

7.125 inches

Distance Between Outside Surfaces Of Hinge Bracket:

8.234 inches

Bottom Mounting Hole Diameter:

0.328 inches

Maximum Rated Armature Speed In Rpm:

8000

Thread Series:

Unf

Thread Class:

2a

Mounting Hole Thread Series Designator:

Unc

Mounting Hole Thread Diameter:

0.375 inches

Mounting Hole Thready Qty Per Inch (tpi):

16

Mounting Hole Thread Class:

2b

Thready Qty Per Inch (tpi):

20

Voltage In Volts:

6.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A14700