

View Online at <https://aerobasegroup.com/nsn/2920-00-351-9608>

Thread Direction:

Right-hand

Thread Length:

0.518 inches

Spline Minor Diameter:

Any acceptable

Spline Major Diameter:

0.874 inches

Spline Width:

0.216 inches

Furnished Items:

Cooling fan and drive pulley

Spline Quantity:

6

Mounting Style:

Bracket mtd w/three mtg holes

Environmental Protection:

Fungus resistant

Submersibility:

Nonsubmersible

Maximum Operating Altitude Rating:

Not rated

Shaft Rotation Direction:

Clockwise

Thread Diameter:

0.625 inches

Spline Length:

1.647 inches

Armature Minimum Speed In Rpm At Full Current Output:

1180

Maximum Output Current Rating In Amps:

55.0

Minimum Current Cut-in Speed In Rpm:

775

Grounding Method:

Internal

Shaft Drive End Style:

Splined shaft end, threaded

Distance Between Shaft Center And Bottom Mounting Hole Center:

4.438 inches

Distance Between Shaft Center And Top Mounting Hole Center:

4.438 inches

Angular Deviation Of First Hole From Top Center In Deg:

196.0

Angular Deviation Of Second Hole From First Hole In Deg:

118.5

Distance Between Inside Surfaces Of Hinge Bracket:

Between 8.774 inches and 8.788 inches

Distance Between Outside Surfaces Of Hinge Bracket:

Between 9.774 inches and 9.778 inches

Top Mounting Hole Diameter:

Between 0.401 inches and 0.411 inches

Bottom Mounting Hole Diameter:

Between 0.526 inches and 0.536 inches

Maximum Rated Armature Speed In Rpm:

5000

Thread Series:

Unf

Thread Class:

2a

Thready Qty Per Inch (tpi):

18

Voltage In Volts:

12.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A14700