NSN 2920-00-351-9608

Engine Accessory Generator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2920-00-351-9608 **Thread Direction:** Right-hand Thread Length: 0.518 inches **Spline Minor Diameter:** Any acceptable **Spline Major Diameter:** 0.874 inches Spline Width: 0.216 inches Furnished Items: Cooling fan and drive pulley Spline Quantity: **Mounting Style:** Bracket mtd w/three mtg holes **Environmental Protection:** Fungus resistant Submersibility: Nonsubmersible **Maximum Operating Altitude Rating:** Not rated **Shaft Rotation Direction:** Clockwise **Thread Diameter:** 0.625 inches Spline Length: 1.647 inches **Armature Minimum Speed In Rpm At Full Current Output:** 1180 **Maximum Output Current Rating In Amps:** Minimum Current Cut-in Speed In Rpm: 775 **Grounding Method:** Internal **Shaft Drive End Style:** Splined shaft end, threaded **Distance Between Shaft Center And Bottom Mounting Hole Center:**

Distance Between Shaft Center And Bottom Mounting Hole Cent
4.438 inches

Distance Between Shaft Center And Top Mounting Hole Center:
4.438 inches

NSN 2920-00-351-9608 Engine Accessory Generator - Page 2 of 2



Angular Deviation Of First Hole From Top Center In Deg:
196.0
Angular Deviation Of Second Hole From First Hole In Deg
118.5
Distance Between Inside Surfaces Of Hinge Bracket:
Between 8.774 inches and 8.788 inches
Distance Between Outside Surfaces Of Hinge Bracket:
Between 9.774 inches and 9.778 inches
Top Mounting Hole Diameter:
Between 0.401 inches and 0.411 inches
Bottom Mounting Hole Diameter:
Between 0.526 inches and 0.536 inches
Maximum Rated Armature Speed In Rpm:
5000
Thread Series:
Unf
Thread Class:
2a
Thready Qty Per Inch (tpi):
18
Voltage In Volts:
12.0
Shelf Life:
N/a
Unit Of Measure:
.
Demilitarization:
Yes - demil/mli
Fiig:
A14700