

View Online at <https://aerobasegroup.com/nsn/2920-00-351-9631>

**Thread Direction:**

Right-hand

**Thread Length:**

0.438 inches

**Furnished Items:**

Woodruff key

**Second Step Diameter:**

Between 0.6245 inches and 0.625 inches

**Keyway Width:**

0.156 inches

**Unthreaded Portion Length:**

0.688 inches

**Mounting Style:**

No mounting provisions

**Environmental Protection:**

Corrosion resistant and fungus resistant

**Keyway Length:**

0.625 inches

**Submersibility:**

Nonsubmersible

**Maximum Operating Altitude Rating:**

Not rated

**Shaft Rotation Direction:**

Counterclockwise

**Distance From End To Keyway Center:**

0.750 inches

**Thread Diameter:**

0.438 inches

**Ground Polarity Type:**

Negative or positive

**Armature Minimum Speed In Rpm At Full Current Output:**

1325

**Maximum Output Current Rating In Amps:**

10.0

**Grounding Method:**

External

**Shaft Drive End Style:**

Straight shaft end, threaded, w/keyway

**Maximum Rated Armature Speed In Rpm:**

1425

**Thread Series:**

Unf

**Thread Class:**

2a

**Thready Qty Per Inch (tpi):**

20

**Voltage In Volts:**

12.0

**Special Features:**

Double end shaft

**Fsc Application Data:**

Engine electrical system, nonaircraft

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A14700