NSN 2920-00-353-6888

Ignition Magneto - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2920-00-353-6888

| Body Material: |
|---|
| - |
| Magnesium |
| Drive Connection Type: |
| |
| Mounting Slot Width: |
| Between 0.403 inches and 0.414 inches |
| Mounting Slot Length: |
| 1.137 inches |
| Environmental Protection: |
| Fungus resistant |
| Distance Between Mounting Facility Centers: |
| Between 4.182 inches and 4.194 inches |
| Performance Type: |
| High tension |
| Shaft Rotation Direction: |
| Clockwise |
| Mounting Facility Quantity: |
| 1 and 1 |
| Pole Quantity: |
| 2 |
| Distributor Cap: |
| Included |
| Mounting Method: |
| Flange |
| Impulse Quantity Per Revolution: |
| 4 |
| Ignition Type For Which Designed: |
| Single |
| Secondary Terminal Type: |
| Push-in |
| Mounting Standard Controlling Agency: |
| Sae |
| Mounting Standard Number: |
| J546 |
| Rotation Element Type: |
| Permanent magnet rotor |
| Contact Set Quantity: |
| 1 |
| Mounting Facility: |
| Slot and threaded hole |
| Features Provided: |
| Radio interference shielding |

NSN 2920-00-353-6888

Ignition Magneto - Page 2 of 2



Spark Distribution Method: Gap Mounting Facility Thread Series: Unc Mounting Facility Thread Diameter: 0.375 inches Mounting Facility Thready Qty Per Inch (tpi): 16 Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A12200