NSN 2920-00-353-7398

Electrical Engine Starter - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/2920-00-353-7398

| Mounting Hole Diameter: |
|---|
| Between 0.479 inches and 0.489 inches |
| Mounting Hole Circle Radius: |
| 2.063 inches |
| Mounting Flange Shape Style: |
| Oval |
| Engaging Mechanism Style: |
| Peripheral outboard gear drive w/worm shaft, shaft, shift lever, collar and over-running clutch w/drive housing |
| Engaging Mechanism Opening Angular Deviation In Deg: |
| 135.0 |
| Lever Actuation Method: |
| Solenoid |
| Lock Test Current Rating In Amps: |
| 410.0 |
| Shaft Rotation Direction: |
| Clockwise |
| Armature Actuation Device Type: |
| Relay-solenoid |
| Engaging Mechanism To Armature Positional Relationship: |
| Straight |
| Mounting Flange Angular Deviation In Deg: |
| 45.0 |
| Voltage In Volts: |
| 6.0 |
| Terminal Type And Quantity: |
| 3 threaded stud |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A23400 |
| |
| |