

View Online at <https://aerobasegroup.com/nsn/2920-00-353-9544>

**Thread Direction:**

Right-hand

**Thread Length:**

0.719 inches

**Furnished Items:**

Voltage regulator

**Second Step Diameter:**

0.668 mils and 0.669 centimeters

**Keyway Width:**

0.125 inches

**Unthreaded Portion Length:**

1.250 inches

**Mounting Hole Thread Direction:**

Right-hand

**Mounting Style:**

Bracket mtd w/three mtg holes, top hole threaded

**Environmental Protection:**

Corrosion resistant and fungus resistant

**Keyway Length:**

0.625 inches

**Submersibility:**

Nonsubmersible

**Shaft Rotation Direction:**

Clockwise

**Distance From End To Keyway Center:**

1.344 inches

**Thread Diameter:**

0.500 inches

**Armature Minimum Speed In Rpm At Full Current Output:**

2200

**Maximum Output Current Rating In Amps:**

10.0

**Grounding Method:**

External

**Shaft Drive End Style:**

Straight shaft end, threaded, w/keyway

**Cotter Pin Hole:**

Included

**Distance Between Shaft Center And Bottom Mounting Hole Center:**

3.062 inches

**Distance Between Shaft Center And Top Mounting Hole Center:**

3.062 inches

**Angular Deviation Of First Hole From Top Center In Deg:**

193.0

**Angular Deviation Of Second Hole From First Hole In Deg:**

164.0

**Distance Between Inside Surfaces Of Hinge Bracket:**

Between 6.118 inches and 6.136 inches

**Distance Between Outside Surfaces Of Hinge Bracket:**

Between 6.868 inches and 6.886 inches

**Bottom Mounting Hole Diameter:**

Between 0.316 inches and 0.324 inches

**Maximum Rated Armature Speed In Rpm:**

2400

**Thread Series:**

Unf

**Thread Class:**

2a

**Mounting Hole Thread Series Designator:**

Unc

**Mounting Hole Thread Diameter:**

0.312 inches

**Mounting Hole Thready Qty Per Inch (tpi):**

18

**Mounting Hole Thread Class:**

2b

**Thready Qty Per Inch (tpi):**

20

**Voltage In Volts:**

12.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A14700