

View Online at <https://aerobasegroup.com/nsn/2920-00-368-6658>

**Body Material:**

Aluminum alloy

**Drive Connection Type:**

Impulse coupled

**Environmental Protection:**

Fungus resistant

**Distance Between Mounting Facility Centers:**

2.204 inches

**Performance Type:**

High tension

**Shaft Rotation Direction:**

Counterclockwise

**Mounting Facility Quantity:**

2

**Pole Quantity:**

2

**Distributor Cap:**

Included

**Mounting Method:**

Base

**Impulse Quantity Per Revolution:**

1

**Ignition Type For Which Designed:**

Single

**Secondary Terminal Type:**

Push-in

**Rotation Element Type:**

Permanent magnet rotor

**Contact Set Quantity:**

1

**Mounting Facility:**

Threaded hole

**Features Provided:**

Radio interference shielding

**Spark Distribution Method:**

Gap

**Mounting Facility Thread Series:**

Unc

**Mounting Facility Thread Diameter:**

0.250 inches

**Mounting Facility Thread Qty Per Inch (tpi):**

20

**Surface Treatment:**

Enamel

**Surface Treatment:**

Enamel

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A12200