

View Online at <https://aerobasegroup.com/nsn/2920-00-371-5087>

**Thread Direction:**

Right-hand

**Thread Length:**

0.720 inches

**Furnished Items:**

Woodruff key

**Second Step Diameter:**

Between 0.6684 inches and 0.699 inches

**Keyway Width:**

0.125 inches

**Unthreaded Portion Length:**

Between 1.280 inches and 1.340 inches

**Mounting Style:**

Bracket mtd w/three mtg holes

**Environmental Protection:**

Corrosion resistant and fungus resistant

**Keyway Length:**

0.625 inches

**Submersibility:**

Nonsubmersible

**Maximum Operating Altitude Rating:**

Not rated

**Shaft Rotation Direction:**

Clockwise

**Distance From End To Keyway Center:**

1.380 inches

**Thread Diameter:**

0.500 inches

**Ground Polarity Type:**

Negative or positive

**Armature Minimum Speed In Rpm At Full Current Output:**

1625

**Maximum Output Current Rating In Amps:**

10.0

**Grounding Method:**

External

**Shaft Drive End Style:**

Straight shaft end, threaded, w/keyway

**Distance Between Shaft Center And Bottom Mounting Hole Center:**

3.875 inches

**Distance Between Shaft Center And Top Mounting Hole Center:**

3.500 inches

**Angular Deviation Of First Hole From Top Center In Deg:**

193.0

**Angular Deviation Of Second Hole From First Hole In Deg:**

159.0

**Distance Between Inside Surfaces Of Hinge Bracket:**

Between 7.243 inches and 7.257 inches

**Distance Between Outside Surfaces Of Hinge Bracket:**

8.250 inches

**Top Mounting Hole Diameter:**

0.453 inches

**Bottom Mounting Hole Diameter:**

0.453 inches

**Maximum Rated Armature Speed In Rpm:**

Not rated

**Thread Series:**

Unf

**Thread Class:**

2a

**Thready Qty Per Inch (tpi):**

20

**Voltage In Volts:**

24.0

**Fsc Application Data:**

Engine electrical system, nonaircraft

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A14700