

View Online at <https://aerobasegroup.com/nsn/2920-00-371-5122>

**Thread Direction:**

Right-hand

**Thread Length:**

0.844 inches

**Spline Minor Diameter:**

Between 0.763 inches and 0.765 inches

**Spline Major Diameter:**

Between 0.875 inches and 0.876 inches

**Spline Width:**

0.196 inches

**Spline Quantity:**

13

**Mounting Hole Thread Direction:**

Right-hand

**Mounting Style:**

Bracket mtd w/three mtg holes, top hole threaded

**Environmental Protection:**

Corrosion resistant and fungus resistant

**Submersibility:**

Nonsubmersible

**Shaft Rotation Direction:**

Clockwise

**Thread Diameter:**

0.625 inches

**Spline Length:**

2.000 inches

**Ground Polarity Type:**

Negative or positive

**Armature Minimum Speed In Rpm At Full Current Output:**

1800

**Maximum Output Current Rating In Amps:**

40.0

**Grounding Method:**

Internal

**Shaft Drive End Style:**

Splined shaft end, threaded

**Distance Between Shaft Center And Bottom Mounting Hole Center:**

3.875 inches

**Distance Between Shaft Center And Top Mounting Hole Center:**

3.875 inches

**Angular Deviation Of First Hole From Top Center In Deg:**

180.0

**Angular Deviation Of Second Hole From First Hole In Deg:**

159.0

**Distance Between Inside Surfaces Of Hinge Bracket:**

Between 7.243 inches and 7.257 inches

**Distance Between Outside Surfaces Of Hinge Bracket:**

Between 8.118 inches and 8.132 inches

**Bottom Mounting Hole Diameter:**

0.453 inches

**Thread Series:**

Unf

**Thread Class:**

2a

**Mounting Hole Thread Series Designator:**

Unc

**Mounting Hole Thread Diameter:**

0.375 inches

**Mounting Hole Thready Qty Per Inch (tpi):**

16

**Mounting Hole Thread Class:**

2b

**Thready Qty Per Inch (tpi):**

18

**Voltage In Volts:**

24.0

**Fsc Application Data:**

Engine electrical system, nonaircraft

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A14700