

View Online at <https://aerobasegroup.com/nsn/2920-00-377-5241>

Thread Direction:

Right-hand

Thread Length:

0.750 inches

Furnished Items:

Cooling fan and woodruff key

Second Step Diameter:

0.8736 mils and 0.8741 centimeters

Keyway Width:

0.156 inches

Unthreaded Portion Length:

1.188 inches

Mounting Hole Depth:

0.500 inches

Countersunk Mounting Hole Angle In Deg:

30.0

Environmental Protection:

Corrosion resistant and fungus resistant

Keyway Length:

0.750 inches

Submersibility:

Nonsubmersible

Shaft Rotation Direction:

Clockwise

Distance From End To Keyway Center:

1.375 inches

Thread Diameter:

0.500 inches

Armature Minimum Speed In Rpm At Full Current Output:

1700

Maximum Output Current Rating In Amps:

20.0

Shaft Drive End Style:

Straight shaft end, threaded, w/keyway

Angular Deviation Of First Hole From Top Center In Deg:

27.0

Angular Deviation Of Second Hole From First Hole In Deg:

288.0

Mounting Hole Largest Diameter:

0.500 inches

Mounting Hole Smallest Diameter:

0.312 inches

Mounting Pilot Outside Diameter:

Between 3.246 inches and 3.248 inches

Distance From Mounting Hole Center To End Of Housing:

Between 1.728 inches and 1.763 inches

Mounting Pilot Depth:

3.000 inches

Thread Series:

Unf

Thread Class:

2a

Thready Qty Per Inch (tpi):

20

Voltage In Volts:

24.0

Fsc Application Data:

Engine electrical system, nonaircraft

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A14700