

View Online at <https://aerobasegroup.com/nsn/2920-00-404-6984>

Thread Direction:

Right-hand

Thread Length:

0.650 inches

Pilot Diameter:

Between 3.247 inches and 3.249 inches

Furnished Items:

Cooling fan and fan shroud and oil deflector and woodruff key

Second Step Diameter:

0.7491 mils and 0.7496 centimeters

Keyway Width:

0.156 inches

Unthreaded Portion Length:

1.320 inches

Mounting Style:

Flange mtd w/three mtg holes

Center To Center Distance Between Mounting Holes Along Width:

Between 3.605 inches and 3.645 inches

Pilot Height:

0.150 mils and 0.170 centimeters

Keyway Length:

0.750 inches

Submersibility:

Nonsubmersible

Shaft Rotation Direction:

Counterclockwise

Distance From End To Keyway Center:

1.312 inches

Thread Diameter:

0.500 inches

Ground Polarity Type:

Negative or positive

Armature Minimum Speed In Rpm At Full Current Output:

1760

Maximum Output Current Rating In Amps:

24.0

Grounding Method:

External

Shaft Drive End Style:

Straight shaft end, threaded, w/keyway

Distance Between Shaft Center And Bottom Mounting Hole Center:

Between 3.052 inches and 3.072 inches

Top Mounting Hole Diameter:

Between 0.470 inches and 0.530 inches

Bottom Mounting Hole Diameter:

Between 0.467 inches and 0.477 inches

Center To Center Distance Between Top Mounting Slot And Bottom Mounting Hole:

Between 5.865 inches and 5.885 inches

Thread Series:

Unf

Thread Class:

2a

Thready Qty Per Inch (tpi):

20

Voltage In Volts:

12.0

Fsc Application Data:

Engine electrical system, nonaircraft

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A14700