

View Online at <https://aerobasegroup.com/nsn/2920-00-410-5727>

Thread Length:

0.420 inches

Unthreaded Portion Length:

1.230 inches

Mounting Hole Thread Direction:

Right-hand

Mounting Style:

Flange mtd w/two mtg holes, top hole threaded

Environmental Protection:

Corrosion resistant and fungus resistant

Submersibility:

Nonsubmersible

Shaft Rotation Direction:

Clockwise or counterclockwise

Ground Polarity Type:

Negative

Armature Minimum Speed In Rpm At Full Current Output:

2000

Maximum Output Current Rating In Amps:

22.0

Rectifier Location:

Separate

Grounding Method:

External

Shaft Drive End Style:

Straight shaft end, threaded

Distance Between Shaft Center And Bottom Mounting Hole Center:

3.300 inches

Distance Between Shaft Center And Top Mounting Hole Center:

3.300 inches

Angular Deviation Of First Hole From Top Center In Deg:

180.0

Angular Deviation Of Second Hole From First Hole In Deg:

180.0

Bottom Mounting Hole Diameter:

0.380 inches

Maximum Rated Armature Speed In Rpm:

5000

Mounting Hole Thread Series Designator:

Unc

Mounting Hole Thread Diameter:

0.562 inches

Mounting Hole Thready Qty Per Inch (tpi):

18

Mounting Hole Thread Class:

2b

Voltage In Volts:

12.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A14700