

View Online at <https://aerobasegroup.com/nsn/2920-00-413-4323>

Thread Direction:

Right-hand

Thread Length:

0.436 inches

Second Step Diameter:

0.669 inches

Unthreaded Portion Length:

0.840 inches

Mounting Hole Thread Direction:

Right-hand

Mounting Style:

Bracket mtd w/three mtg holes, top hole threaded

Submersibility:

Nonsubmersible

Shaft Rotation Direction:

Clockwise

Thread Diameter:

Any acceptable

Maximum Output Current Rating In Amps:

10.0

Shaft Drive End Style:

Straight shaft end, threaded

Distance Between Shaft Center And Bottom Mounting Hole Center:

3.062 inches

Distance Between Shaft Center And Top Mounting Hole Center:

3.060 inches

Angular Deviation Of First Hole From Top Center In Deg:

3.0

Angular Deviation Of Second Hole From First Hole In Deg:

164.0

Distance Between Inside Surfaces Of Hinge Bracket:

6.127 inches

Distance Between Outside Surfaces Of Hinge Bracket:

6.917 inches

Bottom Mounting Hole Diameter:

0.3240 inches

Thread Series:

Unc

Thread Class:

2a

Mounting Hole Thread Series Designator:

Unc

Mounting Hole Thread Diameter:

0.312 inches

Mounting Hole Thready Qty Per Inch (tpi):

18

Mounting Hole Thread Class:

2b

Thready Qty Per Inch (tpi):

Any acceptable

Voltage In Volts:

12.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A14700