

View Online at <https://aerobasegroup.com/nsn/2920-00-420-8890>

Thread Length:

0.594 inches

Second Step Diameter:

0.749 inches

Keyway Width:

0.125 inches

Unthreaded Portion Length:

1.310 inches

Mounting Hole Thread Direction:

Right-hand

Mounting Style:

Bracket mtd w/three mtg holes, top hole threaded

Keyway Length:

0.625 inches

Submersibility:

Nonsubmersible

Shaft Rotation Direction:

Clockwise

Maximum Output Current Rating In Amps:

30.0

Rectifier Location:

Separate

Shaft Drive End Style:

Straight shaft end, threaded, w/keyway

Distance Between Shaft Center And Bottom Mounting Hole Center:

3.250 inches

Distance Between Shaft Center And Top Mounting Hole Center:

3.250 inches

Angular Deviation Of First Hole From Top Center In Deg:

13.0

Angular Deviation Of Second Hole From First Hole In Deg:

180.0

Distance Between Inside Surfaces Of Hinge Bracket:

7.125 inches

Distance Between Outside Surfaces Of Hinge Bracket:

8.275 inches

Bottom Mounting Hole Diameter:

0.518 inches

Maximum Rated Armature Speed In Rpm:

2240

Mounting Hole Thread Series Designator:

Unc

Mounting Hole Thread Diameter:

0.438 inches

Mounting Hole Thready Qty Per Inch (tpi):

14

Mounting Hole Thread Class:

2b

Voltage In Volts:

12.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A14700