

View Online at <https://aerobasegroup.com/nsn/2920-00-439-2872>

Thread Direction:

Right-hand

Thread Length:

0.828 inches

Furnished Items:

Radio interference shielding

Second Step Diameter:

0.780 inches

Keyway Width:

Between 0.186 inches and 0.188 inches

Unthreaded Portion Length:

1.297 inches

Mounting Hole Thread Direction:

Right-hand

Mounting Style:

Bracket mtd w/three mtg holes, top hole threaded

Environmental Protection:

Corrosion resistant and fungus resistant

Submersibility:

Submersible

Maximum Operating Altitude Rating:

10000.0 feet

Shaft Rotation Direction:

Clockwise

Distance From End To Keyway Center:

1.062 inches

Thread Diameter:

0.750 inches

Ground Polarity Type:

Negative

Maximum Output Current Rating In Amps:

230.0

Grounding Method:

Internal

Shaft Drive End Style:

Straight shaft end, threaded, w/keyway

Distance Between Shaft Center And Bottom Mounting Hole Center:

4.688 inches

Distance Between Shaft Center And Top Mounting Hole Center:

Between 4.375 inches and 4.875 inches

Angular Deviation Of First Hole From Top Center In Deg:

170.0

Angular Deviation Of Second Hole From First Hole In Deg:

190.0

Distance Between Inside Surfaces Of Hinge Bracket:

6.125 inches

Distance Between Outside Surfaces Of Hinge Bracket:

7.125 inches

Bottom Mounting Hole Diameter:

Between 0.441 inches and 0.461 inches

Maximum Rated Armature Speed In Rpm:

3000

Thread Series:

Unf

Thread Class:

2a

Mounting Hole Thread Series Designator:

Unc

Mounting Hole Thread Diameter:

0.375 inches

Mounting Hole Thready Qty Per Inch (tpi):

16

Mounting Hole Thread Class:

2b

Thready Qty Per Inch (tpi):

16

Voltage In Volts:

28.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A14700