

View Online at <https://aerobasegroup.com/nsn/2920-00-444-7100>

Thread Direction:

Right-hand

Thread Length:

0.406 inches

Pilot Diameter:

2.000 inches

Furnished Items:

Woodruff key and nut and bushing package and fan pulley

Second Step Diameter:

0.625 inches

Keyway Width:

0.125 inches

Unthreaded Portion Length:

1.094 inches

Mounting Hole Thread Direction:

Right-hand

Center To Center Distance Between Mounting Holes Along Width:

1.688 inches

Pilot Height:

0.312 inches

Keyway Length:

0.500 inches

Submersibility:

Nonsubmersible

Shaft Rotation Direction:

Clockwise or counterclockwise

Distance From End To Keyway Center:

0.812 inches

Thread Diameter:

0.625 inches

Ground Polarity Type:

Negative

Maximum Output Current Rating In Amps:

55.0

Rectifier Location:

Integral

Grounding Method:

Internal

Shaft Drive End Style:

Straight shaft end, threaded, w/keyway

Distance Between Shaft Center And Bottom Mounting Hole Center:

3.500 inches

Top Mounting Hole Diameter:

0.250 inches

Bottom Mounting Hole Diameter:

0.500 inches

Center To Center Distance Between Top Mounting Slot And Bottom Mounting Hole:

6.250 inches

Thread Series:

Unf

Thread Class:

2a

Mounting Hole Thread Series Designator:

Unc

Mounting Hole Thread Diameter:

0.250 inches

Mounting Hole Thready Qty Per Inch (tpi):

20

Mounting Hole Thread Class:

2b

Thready Qty Per Inch (tpi):

18

Voltage In Volts:

12.0

Special Features:

End item: grumman aircraft, model a10

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A14700