

View Online at <https://aerobasegroup.com/nsn/2920-00-450-0025>

Thread Direction:

Right-hand

Thread Length:

0.450 inches

Furnished Items:

Lockwasher and nut

Second Step Diameter:

Between 0.668 inches and 0.669 inches

Unthreaded Portion Length:

Between 0.740 inches and 0.840 inches

Mounting Hole Thread Direction:

Right-hand

Mounting Style:

Flange mtd w/two mtg holes, top hole threaded

Environmental Protection:

Corrosion resistant and fungus resistant

Submersibility:

Nonsubmersible

Shaft Rotation Direction:

Clockwise or counterclockwise

Ground Polarity Type:

Negative

Rectifier Location:

Integral

Shaft Drive End Style:

Straight shaft end, threaded

Distance Between Shaft Center And Bottom Mounting Hole Center:

3.300 inches

Distance Between Shaft Center And Top Mounting Hole Center:

3.300 inches

Angular Deviation Of First Hole From Top Center In Deg:

0.0

Angular Deviation Of Second Hole From First Hole In Deg:

180.0

Bottom Mounting Hole Diameter:

Between 0.378 inches and 0.382 inches

Mounting Hole Thread Series Designator:

Unc

Mounting Hole Thread Diameter:

0.312 inches

Mounting Hole Thread Qty Per Inch (tpi):

18

Mounting Hole Thread Class:

2b

Voltage In Volts:

12.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A14700