

View Online at <https://aerobasegroup.com/nsn/2920-00-451-2783>

**Thread Direction:**

Right-hand

**Thread Length:**

0.650 inches

**Pilot Diameter:**

Between 3.247 inches and 3.249 inches

**Furnished Items:**

Cooling fan and cooling blast tube and lockwasher and nut and woodruff key

**Second Step Diameter:**

Between 0.749 inches and 0.750 inches

**Keyway Width:**

0.156 inches

**Unthreaded Portion Length:**

1.320 inches

**Mounting Style:**

Flange mtd w/three mtg holes

**Center To Center Distance Between Mounting Holes Along Width:**

Between 3.604 inches and 3.644 inches

**Pilot Height:**

Between 0.467 inches and 0.473 inches

**Keyway Length:**

0.750 inches

**Submersibility:**

Nonsubmersible

**Shaft Rotation Direction:**

Counterclockwise

**Distance From End To Keyway Center:**

1.310 inches

**Thread Diameter:**

0.500 inches

**Grounding Method:**

External

**Shaft Drive End Style:**

Straight shaft end, threaded, w/keyway

**Distance Between Shaft Center And Bottom Mounting Hole Center:**

3.062 inches

**Top Mounting Hole Diameter:**

Between 0.623 inches and 0.633 inches

**Bottom Mounting Hole Diameter:**

Between 0.466 inches and 0.476 inches

**Center To Center Distance Between Top Mounting Slot And Bottom Mounting Hole:**

5.875 inches

**Thread Series:**

Unf

**Thread Class:**

2a

**Thready Qty Per Inch (tpi):**

20

**Voltage In Volts:**

24.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A14700