

View Online at <https://aerobasegroup.com/nsn/2920-00-460-5494>

Thread Direction:

Right-hand

Second Step Diameter:

Between 0.873 inches and 0.874 inches

Mounting Hole Thread Direction:

Right-hand

Mounting Style:

Bracket mtd w/three mtg holes, top hole threaded

Submersibility:

Nonsubmersible

Shaft Rotation Direction:

Clockwise

Thread Diameter:

0.625 inches

Maximum Output Current Rating In Amps:

35.0

Rectifier Location:

Separate

Shaft Drive End Style:

Straight shaft end, threaded

Distance Between Shaft Center And Bottom Mounting Hole Center:

3.590 inches

Distance Between Shaft Center And Top Mounting Hole Center:

3.900 inches

Angular Deviation Of First Hole From Top Center In Deg:

180.0

Angular Deviation Of Second Hole From First Hole In Deg:

180.0

Distance Between Inside Surfaces Of Hinge Bracket:

3.975 inches

Distance Between Outside Surfaces Of Hinge Bracket:

5.195 inches

Bottom Mounting Hole Diameter:

0.518 inches

Thread Series:

Unf

Thread Class:

2a

Mounting Hole Thread Series Designator:

Uns

Mounting Hole Thread Diameter:

0.500 inches

Mounting Hole Thready Qty Per Inch (tpi):

14-1/2

Mounting Hole Thread Class:

2b

Thready Qty Per Inch (tpi):

18

Voltage In Volts:

24.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A14700