## NSN 2920-00-477-6099

Electrical Engine Starter Relay-solenoid - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/2920-00-477-6099    |
|--|
| Mounting Hole Diameter:  |
| 0.315 mils and 0.335 centimeters                                 |
| Mounting Slot Width:   |
| Between 0.255 inches and 0.265 inches                            |
| Mounting Slot Length:  |
| Between 0.315 inches and 0.335 inches                            |
| Submersibility:  |
| Nonsubmersible   |
| Mounting Facility Spacing:                                       |
| Holes 1.400 in. C to c slots 1.400 in. C to c 66 degrees apart   |
| Voltage Rating:  |
| 12.0 volts   |
| Pull-in Current:   |
| Between 70.5 amperes and 77.8 amperes                            |
| Hold-in Current:   |
| 18.0 volt-ampere and 20.0 microwatts                             |
| Engaging Linkage:  |
| Not included   |
| Contact Manual Closing Provision:                                |
| Not included   |
| Control Terminal Quantity:                                       |
| 1  |
| Control Terminal Type:   |
| Stud   |
| Grounded Control Terminal:                                       |
| Included   |
| Main Terminal Quantity:  |
| 2  |
| Main Terminal Type:  |
| Stud   |
| Control Terminal Quantity Internally Connected To Main Terminal: |
| 1  |
| Motor Diameter For Which Rigid Mount Is Designed:                |
| 5.062 inches   |
| Mounting Facility Type And Quantity:                             |
| 2 hole and 2 slot  |
| Special Features:  |
| Fungus and corrosion resistant and waterproof                    |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |

--

## NSN 2920-00-477-6099

Electrical Engine Starter Relay-solenoid - Page 2 of 2



Demilitarization:

No

Fiig:

T130-h