NSN 2920-00-477-6099

Electrical Engine Starter Relay-solenoid - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2920-00-477-6099
Mounting Hole Diameter:
0.315 mils and 0.335 centimeters
Mounting Slot Width:
Between 0.255 inches and 0.265 inches
Mounting Slot Length:
Between 0.315 inches and 0.335 inches
Submersibility:
Nonsubmersible
Mounting Facility Spacing:
Holes 1.400 in. C to c slots 1.400 in. C to c 66 degrees apart
Voltage Rating:
12.0 volts
Pull-in Current:
Between 70.5 amperes and 77.8 amperes
Hold-in Current:
18.0 volt-ampere and 20.0 microwatts
Engaging Linkage:
Not included
Contact Manual Closing Provision:
Not included
Control Terminal Quantity:
1
Control Terminal Type:
Stud
Grounded Control Terminal:
Included
Main Terminal Quantity:
2
Main Terminal Type:
Stud
Control Terminal Quantity Internally Connected To Main Terminal:
1
Motor Diameter For Which Rigid Mount Is Designed:
5.062 inches
Mounting Facility Type And Quantity:
2 hole and 2 slot
Special Features:
Fungus and corrosion resistant and waterproof
Shelf Life:
N/a
Unit Of Measure:

--

NSN 2920-00-477-6099

Electrical Engine Starter Relay-solenoid - Page 2 of 2



Demilitarization:

No

Fiig:

T130-h