NSN 2920-00-500-7366

Electrical Engine Starter Relay-solenoid - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2920-00-500-7366 **Mounting Slot Width:** 0.275 inches **Mounting Slot Length:** 0.465 inches Submersibility: Nonsubmersible **Mounting Facility Spacing:** 1.750 in. C to c 75 degrees apart Voltage Rating: 24.0 volts **Pull-in Current:** Between 25.0 amperes and 39.0 amperes **Hold-in Current:** 5.75 volt-ampere and 6.75 microwatts **Plunger Stroke Length:** 0.500 inches **Engaging Linkage:** Not included Accommodated Linkage Threaded Hole Thread Size: 3/8-20 **Contact Manual Closing Provision:** Not included **Control Terminal Quantity: Control Terminal Type:** Stud **Grounded Control Terminal:** Included **Main Terminal Quantity: Main Terminal Type: Control Terminal Quantity Internally Connected To Main Terminal:** Motor Diameter For Which Rigid Mount Is Designed: 4.438 inches **Mounting Facility Type And Quantity:** 4 slot **Special Features:** End item: grumman aircraft, model a10; fungus and mildew resistant Shelf Life:

N/a

NSN 2920-00-500-7366

Electrical Engine Starter Relay-solenoid - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

T130-h