## NSN 2920-00-518-9704

Electrical Engine Starter Relay-solenoid - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2920-00-518-9704 **Mounting Slot Width:** 0.281 inches **Mounting Slot Length:** 0.343 inches Submersibility: Nonsubmersible **Mounting Facility Spacing:** 1.750 in. C to c 66 degrees apart on 2.562 in. Radius Voltage Rating: 24.0 volts **Pull-in Current:** Between 41.6 amperes and 45.8 amperes **Hold-in Current:** 7.3 volt-ampere and 8.3 microwatts **Plunger Stroke Length:** 0.750 inches **Engaging Linkage:** Not included Accommodated Linkage Threaded Hole Thread Size: 1/2-20 **Contact Manual Closing Provision:** Not included **Control Terminal Quantity: Control Terminal Type:** Stud **Grounded Control Terminal:** Included **Main Terminal Quantity: Main Terminal Type: Control Terminal Quantity Internally Connected To Main Terminal:** Motor Diameter For Which Rigid Mount Is Designed: 5.120 inches **Mounting Facility Type And Quantity:** 4 slot Shelf Life: N/a

Unit Of Measure:

## NSN 2920-00-518-9704

Electrical Engine Starter Relay-solenoid - Page 2 of 2



_						
ם ו	mil	11+2	riz	21 to	$\alpha$ r	٠.
DС		IILa	114	аи	v	ı.

No

Fiig:

T130-h