NSN 2920-00-529-7297

Engine Accessory Generator - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/2920-00-529-7297 | 7 |
|---|---|
| Thread Pitch Diameters: | |
| +0.6324 to 0.6365 inches | |
| Thread Direction: | |
| Right-hand | |
| Thread Length: | |
| Between 1.458 inches and 1.518 inches | |
| Furnished Items: | |
| Woodruff key | |
| Second Step Diameter: | |
| Between 0.6684 inches and 0.669 inches | |
| Keyway Width: | |
| 0.125 inches | |
| Unthreaded Portion Length: | |
| Between 1.280 inches and 1.340 inches | |
| Mounting Hole Thread Direction: | |
| Right-hand | |
| Mounting Style: | |
| Bracket mtd w/three mtg holes, top hole threaded | |
| Environmental Protection: | |
| Corrosion resistant and fungus resistant | |
| Keyway Length: | |
| 0.625 inches | |
| Submersibility: | |
| Nonsubmersible | |
| Maximum Operating Altitude Rating: | |
| Not rated | |
| Shaft Rotation Direction: | |
| Clockwise | |
| Distance From End To Keyway Center: | |
| 1.140 inches | |
| Thread Diameter: | |
| 0.669 inches | |
| Ground Polarity Type: | |
| Negative or positive | |
| Armature Minimum Speed In Rpm At Full Current Output: | |
| 1900 | |
| Maximum Output Current Rating In Amps: | |
| 18.0 | |
| Grounding Method: | |
| External | |
| Shaft Drive End Style: | |

Shaft Drive End Style:

Straight shaft end, threaded, w/keyway

NSN 2920-00-529-7297

Engine Accessory Generator - Page 2 of 2



| Distance Between Shaft Center And Bottom Mounting Hole Center: |
|--|
| 3.875 inches |
| Distance Between Shaft Center And Top Mounting Hole Center: |
| 3.500 inches |
| Angular Deviation Of First Hole From Top Center In Deg: |
| 193.0 |
| Angular Deviation Of Second Hole From First Hole In Deg: |
| 159.0 |
| Distance Between Inside Surfaces Of Hinge Bracket: |
| Between 7.243 inches and 7.657 inches |
| Distance Between Outside Surfaces Of Hinge Bracket: |
| Between 8.123 inches and 8.137 inches |
| Bottom Mounting Hole Diameter: |
| 0.453 inches |
| Maximum Rated Armature Speed In Rpm: |
| Not rated |
| Thread Series: |
| Uns |
| Mounting Hole Thread Series Designator: |
| Unc |
| Mounting Hole Thread Diameter: |
| 0.375 inches |
| Mounting Hole Thready Qty Per Inch (tpi): |
| 16 |
| Mounting Hole Thread Class: |
| 2b |
| Thready Qty Per Inch (tpi): |
| 20 |
| Voltage In Volts: |
| 24.0 |
| Fsc Application Data: |
| Engine electrical system, nonaircraft |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A14700 |