## NSN 2920-00-540-8352

Spark Plug - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/2920-00-540-8352

3 · · · · · · · · · · · · · · · · · · ·
Body Style:
Unshielded, threaded post, gasket seat
End Application:
Shipboard material handling equipment (mhe); aircraft, phantom f-4; missle, minuteman lgm-30; support equipment, h-3 helicopter; shop
equipment contact maintenance, truck mounted; mercy and comfort hospital ships class tah; usns henry j. Kaiser class tao; support
equipment, b-52 aircraft; truck, forklift-gas 4000lb 144-in
Reach Length:
0.500 inches
Usage Design:
Engine other than aircraft
Width Across Flats:
0.875 inches
Electrode Style:
Single flat shell ground electrode (see also style 4)
Thread Size And Series/type Designator And Location:
18-1.5mm base
Mean Effective Pressure Rating:
160.0 pounds per square inch
Seat Major Diameter:
1.000 inches
Height Above Mounting Surface:
2.320 inches
Criticality Code Justification:
Feat
Special Features:
Grumman aerospace corporation a10 aircraft; weapon system essential
Test Data Document:
81348-ws506 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Or Standard:
3 type and b class
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:

Fiig:

No

A10400