

View Online at <https://aerobasegroup.com/nsn/2920-00-541-9814>

Thread Direction:

Right-hand

Thread Length:

0.250 inches

Pilot Diameter:

Between 2.684 inches and 2.686 inches

Furnished Items:

Cooling blast tube and radio interference shielding

Second Step Diameter:

0.669 inches

Keyway Width:

0.094 inches

Mounting Hole Diameter:

0.344 inches

Mounting Hole Circle Radius:

1.828 inches

Unthreaded Portion Length:

1.580 inches

Pilot Height:

0.190 inches

Environmental Protection:

Corrosion resistant and fungus resistant

Keyway Length:

0.500 inches

Submersibility:

Nonsubmersible

Shaft Rotation Direction:

Clockwise

Distance From End To Keyway Center:

1.550 inches

Thread Diameter:

0.312 inches

Ground Polarity Type:

Negative or positive

Armature Minimum Speed In Rpm At Full Current Output:

3100

Maximum Output Current Rating In Amps:

15.0

Minimum Current Cut-in Speed In Rpm:

1600

Grounding Method:

External

Shaft Drive End Style:

Straight shaft end, threaded, w/keyway

Angular Deviation Of First Hole From Top Center In Deg:

30.0

Angular Deviation Of Second Hole From First Hole In Deg:

120.0

Angular Deviation Of Third Hole From Second Hole In Deg:

120.0

Thread Series:

Unf

Thread Class:

2a

Thready Qty Per Inch (tpi):

24

Voltage In Volts:

24.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A14700