

View Online at <https://aerobasegroup.com/nsn/2920-00-555-2205>

Thread Direction:

Right-hand

Thread Length:

0.781 inches

Furnished Items:

Cooling fan and drive pulley and woodruff key

Taper Length:

1.344 inches

Keyway Width:

0.250 inches

Mounting Hole Thread Direction:

Right-hand

Keyway Length:

1.000 inches

Largest Diameter:

1.125 inches

Submersibility:

Nonsubmersible

Shaft Rotation Direction:

Clockwise or counterclockwise

Distance From End To Keyway Center:

1.469 inches

Thread Diameter:

0.750 inches

Armature Minimum Speed In Rpm At Full Current Output:

1050

Maximum Output Current Rating In Amps:

70.0

Minimum Current Cut-in Speed In Rpm:

550

Rectifier Location:

Separate

Shaft Drive End Style:

Tapered shaft end, threaded w/keyway

Distance From Raised Face To First Mounting Hole Center:

2.906 inches

Angular Deviation Of First Hole From Top Center In Deg:

90.0

Angular Deviation Of Second Hole From First Hole In Deg:

90.0

Distance From Raised Face To Second Mounting Center:

8.406 inches

Angular Deviation Of Third Hole From Second Hole In Deg:

90.0

Angular Deviation Of Fourth Hole From Third Hole In Deg:

90.0

Maximum Rated Armature Speed In Rpm:

8000

Thread Series:

Unf

Thread Class:

2a

Mounting Hole Thread Series Designator:

Unc

Mounting Hole Thread Diameter:

0.500 inches

Mounting Hole Thready Qty Per Inch (tpi):

13

Mounting Hole Thread Class:

2b

Thready Qty Per Inch (tpi):

16

Voltage In Volts:

28.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A14700