

View Online at <https://aerobasegroup.com/nsn/2920-00-561-9972>

Body Material:

Steel

Drive Connection Type:

Impulse coupled

Mounting Slot Width:

0.438 inches

Mounting Slot Length:

1.188 inches

Shaft Length:

1.078 inches

Distance Between Mounting Facility Centers:

Between 4.184 inches and 4.190 inches

Performance Type:

High tension

Drive Shaft Type:

Keyway shaft

Shaft Rotation Direction:

Clockwise

Mounting Facility Quantity:

1

Pole Quantity:

2

Distributor Cap:

Included

Mounting Method:

Flange

Impulse Quantity Per Revolution:

2

Ignition Type For Which Designed:

Single

Secondary Terminal Type:

Threaded

Spark Plug Terminal Accommodation Thread Series:

Unef

Rotation Element Type:

Permanent magnet rotor

Contact Set Quantity:

1

Mounting Facility:

Slot and threaded hole

Features Provided:

Radio interference shielding

Spark Distribution Method:

Gap

Spark Plug Terminal Accommodation Thread Diameter:

0.688 inches

Spark Plug Terminal Accommodation Thread Qty Per Inch (tpi):

24

Mounting Facility Thread Series:

Unc

Mounting Facility Thread Diameter:

0.188 inches

Mounting Facility Thread Qty Per Inch (tpi):

16

Surface Treatment:

Paint

Surface Treatment:

Paint

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A12200