

View Online at <https://aerobasegroup.com/nsn/2920-00-573-0455>

Thread Direction:

Right-hand

Thread Length:

0.375 inches

Pilot Diameter:

Between 2.995 inches and 2.999 inches

Furnished Items:

Nut and voltage regulator and woodruff key

Second Step Diameter:

Between 0.749 inches and 0.750 inches

Keyway Width:

0.156 inches

Unthreaded Portion Length:

1.062 inches

Mounting Style:

Flange mtd w/two mtg holes

Pilot Height:

0.375 inches

Keyway Length:

0.750 inches

Submersibility:

Nonsubmersible

Shaft Rotation Direction:

Clockwise

Distance From End To Keyway Center:

0.906 inches

Thread Diameter:

0.500 inches

Maximum Output Current Rating In Amps:

16.0

Rectifier Location:

Integral

Shaft Drive End Style:

Straight shaft end, threaded, w/keyway

Distance Between Shaft Center And Bottom Mounting Hole Center:

2.750 inches

Distance Between Shaft Center And Top Mounting Hole Center:

2.750 inches

Angular Deviation Of First Hole From Top Center In Deg:

0.0

Angular Deviation Of Second Hole From First Hole In Deg:

180.0

Top Mounting Hole Diameter:

0.531 inches

Bottom Mounting Hole Diameter:

0.531 inches

Maximum Rated Armature Speed In Rpm:

2000

Thread Series:

Unf

Thread Class:

2a

Thready Qty Per Inch (tpi):

20

Voltage In Volts:

6.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A14700