

View Online at <https://aerobasegroup.com/nsn/2920-00-582-3924>

Thread Direction:

Right-hand

Thread Length:

0.492 inches

Second Step Diameter:

0.590 inches

Keyway Width:

Between 0.125 inches and 0.126 inches

Unthreaded Portion Length:

0.708 inches

Mounting Hole Thread Direction:

Right-hand

Mounting Style:

Bracket mtd w/three mtg holes, top hole threaded

Keyway Length:

0.500 inches

End Application:

Grumman a10 aircraft

Submersibility:

Nonsubmersible

Shaft Rotation Direction:

Clockwise

Distance From End To Keyway Center:

0.789 inches

Thread Diameter:

0.437 inches

Shaft Drive End Style:

Straight shaft end, threaded, w/keyway

Distance Between Shaft Center And Bottom Mounting Hole Center:

Between 2.995 inches and 3.005 inches

Distance Between Shaft Center And Top Mounting Hole Center:

Between 2.995 inches and 3.005 inches

Angular Deviation Of First Hole From Top Center In Deg:

27.0

Angular Deviation Of Second Hole From First Hole In Deg:

220.0

Distance Between Inside Surfaces Of Hinge Bracket:

Between 5.678 inches and 5.693 inches

Distance Between Outside Surfaces Of Hinge Bracket:

Between 5.745 inches and 5.776 inches

Bottom Mounting Hole Diameter:

Between 0.312 inches and 0.316 inches

Thread Series:

Unf

Thread Class:

2a

Mounting Hole Thread Series Designator:

Unc

Mounting Hole Thread Diameter:

0.312 inches

Mounting Hole Thready Qty Per Inch (tpi):

18

Mounting Hole Thread Class:

2b

Thready Qty Per Inch (tpi):

20

Voltage In Volts:

12.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A14700