

View Online at <https://aerobasegroup.com/nsn/2920-00-585-0883>

**Body Material:**

Steel

**Drive Connection Type:**

Helical gear

**Furnished Items:**

Ignition coil

**Shaft Length:**

1.500 inches

**Environmental Protection:**

Submersible and fungus resistant

**Drive Shaft Type:**

Keyway shaft

**Shaft Rotation Direction:**

Counterclockwise

**Distributor Cap:**

Included

**Mounting Method:**

Clamp

**Impulse Quantity Per Revolution:**

6

**Ignition Type For Which Designed:**

Single

**Secondary Terminal Type:**

Threaded

**Spark Plug Terminal Accommodation Thread Series:**

Unef

**Primary Terminal Accommodation Type:**

Stud

**Spark Advance Control Method:**

Centrifugal

**Maximum Advance Deg:**

5.0

**Contact Set Quantity:**

1

**Rpm At Maximum Advance:**

1200.0

**Primary Terminal Accommodation Thread Series:**

Unef

**Features Provided:**

Radio interference shielding

**Spark Distribution Method:**

Gap

**Spark Plug Terminal Accommodation Thread Diameter:**

0.625 inches

**Spark Plug Terminal Accommodation Thread Qty Per Inch (tpi):**

24

**Primary Terminal Accommodation Thread Diameter:**

0.750 inches

**Primary Terminal Accommodation Thread Qty Per Inch (tpi):**

20

**Surface Treatment:**

Paint

**Surface Treatment:**

Paint

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A12200