

View Online at <https://aerobasegroup.com/nsn/2920-00-597-9541>

Thread Direction:

Right-hand

Thread Length:

0.830 inches

Furnished Items:

Lockwasher and nut and woodruff key

Second Step Diameter:

0.874 inches

Keyway Width:

0.156 inches

Unthreaded Portion Length:

1.320 inches

Mounting Style:

Bracket mtd w/two mtg holes

Keyway Length:

0.750 inches

Submersibility:

Nonsubmersible

Shaft Rotation Direction:

Clockwise or counterclockwise

Thread Diameter:

0.625 inches

Ground Polarity Type:

Negative

Armature Minimum Speed In Rpm At Full Current Output:

1100

Maximum Output Current Rating In Amps:

62.0

Rectifier Location:

Integral

Shaft Drive End Style:

Straight shaft end, threaded, w/keyway

Distance Between Shaft Center And Bottom Mounting Hole Center:

3.830 inches

Angular Deviation Of First Hole From Top Center In Deg:

180.0

Distance Between Inside Surfaces Of Hinge Bracket:

3.965 inches

Distance Between Outside Surfaces Of Hinge Bracket:

5.105 inches

Bottom Mounting Hole Diameter:

Between 0.451 inches and 0.463 inches

Maximum Rated Armature Speed In Rpm:

2500

Thread Series:

Unf

Thread Class:

2a

Thready Qty Per Inch (tpi):

18

Voltage In Volts:

12.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A14700