

View Online at <https://aerobasegroup.com/nsn/2920-00-602-4259>

**Body Material:**

Aluminum alloy

**Drive Connection Type:**

Impulse coupled

**Mounting Slot Width:**

Between 0.403 inches and 0.414 inches

**Mounting Slot Length:**

1.137 inches

**Distance Between Mounting Facility Centers:**

Between 4.182 inches and 4.194 inches

**Performance Type:**

High tension

**Shaft Rotation Direction:**

Clockwise

**Mounting Facility Quantity:**

1 and 1

**Pole Quantity:**

2

**Distributor Cap:**

Included

**Mounting Method:**

Flange

**Impulse Quantity Per Revolution:**

4

**Ignition Type For Which Designed:**

Single

**Secondary Terminal Type:**

Push-in

**Mounting Standard Controlling Agency:**

Sae

**Mounting Standard Number:**

J546

**Rotation Element Type:**

Permanent magnet rotor

**Contact Set Quantity:**

1

**Mounting Facility:**

Slot and threaded hole

**Features Provided:**

Radio interference shielding

**Spark Distribution Method:**

Gap

**Mounting Facility Thread Series:**

Unc

**Mounting Facility Thread Diameter:**

0.375 inches

**Mounting Facility Thready Qty Per Inch (tpi):**

16

**Special Features:**

Grumman a10 aircraft

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A12200