

View Online at <https://aerobasegroup.com/nsn/2920-00-605-0737>

Thread Direction:

Right-hand

Thread Length:

0.688 inches

Pilot Diameter:

Between 3.247 inches and 3.249 inches

Slot Width:

Between 0.531 inches and 0.609 inches

Slot Length:

1.219 inches

Second Step Diameter:

0.750 inches

Keyway Width:

0.156 inches

Unthreaded Portion Length:

1.343 inches

Mounting Style:

Flange mtd w/two mtg slots and one mtg hole

Pilot Height:

0.822 inches

Environmental Protection:

Fungus resistant

Keyway Length:

0.750 inches

Center To Center Distance Between Mounting Slots:

3.625 inches

Submersibility:

Nonsubmersible

Shaft Rotation Direction:

Counterclockwise

Distance From End To Keyway Center:

1.428 inches

Thread Diameter:

0.500 inches

Ground Polarity Type:

Negative

Armature Minimum Speed In Rpm At Full Current Output:

3000

Maximum Output Current Rating In Amps:

40.0

Minimum Current Cut-in Speed In Rpm:

2300

Grounding Method:

Internal

Shaft Drive End Style:

Straight shaft end, threaded, w/keyway

Distance Between Shaft Center And Bottom Mounting Hole Center:

3.062 inches

Bottom Mounting Hole Diameter:

0.484 inches

Center To Center Distance Between Top Mounting Slot And Bottom Mounting Hole:

5.875 inches

Maximum Rated Armature Speed In Rpm:

6000

Thread Series:

Unf

Thread Class:

3a

Thready Qty Per Inch (tpi):

20

Voltage In Volts:

24.0

Special Features:

Shielded to prevent radio interference

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A14700