

View Online at <https://aerobasegroup.com/nsn/2920-00-624-9017>

**Thread Direction:**

Right-hand

**Thread Length:**

0.688 inches

**Spline Minor Diameter:**

0.874 inches

**Spline Major Diameter:**

0.875 inches

**Spline Width:**

0.217 inches

**Furnished Items:**

Drive pulley

**Spline Quantity:**

6

**Mounting Hole Thread Direction:**

Right-hand

**Mounting Style:**

Bracket mtd w/three mtg holes, top hole threaded

**Environmental Protection:**

Corrosion resistant and fungus resistant

**Shaft Rotation Direction:**

Clockwise

**Thread Diameter:**

0.625 inches

**Spline Length:**

Between 2.306 inches and 2.346 inches

**Armature Minimum Speed In Rpm At Full Current Output:**

600

**Maximum Output Current Rating In Amps:**

55.0

**Minimum Current Cut-in Speed In Rpm:**

400

**Rectifier Location:**

Separate

**Grounding Method:**

Internal

**Shaft Drive End Style:**

Splined shaft end, threaded

**Angular Deviation Of First Hole From Top Center In Deg:**

15.0

**Angular Deviation Of Second Hole From First Hole In Deg:**

195.0

**Distance Between Inside Surfaces Of Hinge Bracket:**

6.062 inches

**Distance Between Outside Surfaces Of Hinge Bracket:**

7.250 inches

**Bottom Mounting Hole Diameter:**

Between 0.627 inches and 0.629 inches

**Maximum Rated Armature Speed In Rpm:**

1125

**Thread Series:**

Unf

**Mounting Hole Thread Series Designator:**

Unf

**Mounting Hole Thread Diameter:**

0.438 inches

**Mounting Hole Thready Qty Per Inch (tpi):**

20

**Thready Qty Per Inch (tpi):**

18

**Voltage In Volts:**

24.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A14700