

View Online at <https://aerobasegroup.com/nsn/2920-00-640-7492>

Thread Direction:

Right-hand

Thread Length:

0.719 inches

Furnished Items:

Overload protective device

Second Step Diameter:

Between 0.688 inches and 0.689 inches

Keyway Width:

0.125 inches

Unthreaded Portion Length:

1.312 inches

Mounting Hole Thread Direction:

Right-hand

Mounting Style:

Bracket mtd w/three mtg holes, top hole threaded

Keyway Length:

0.625 inches

Submersibility:

Nonsubmersible

Shaft Rotation Direction:

Clockwise

Distance From End To Keyway Center:

1.375 inches

Thread Diameter:

0.500 inches

Armature Minimum Speed In Rpm At Full Current Output:

1850

Maximum Output Current Rating In Amps:

40.0

Minimum Current Cut-in Speed In Rpm:

1600

Grounding Method:

Internal

Shaft Drive End Style:

Straight shaft end, threaded, w/keyway

Distance Between Shaft Center And Bottom Mounting Hole Center:

3.785 inches

Distance Between Shaft Center And Top Mounting Hole Center:

3.500 inches

Angular Deviation Of First Hole From Top Center In Deg:

193.0

Angular Deviation Of Second Hole From First Hole In Deg:

159.0

Distance Between Inside Surfaces Of Hinge Bracket:

Between 7.243 inches and 7.257 inches

Distance Between Outside Surfaces Of Hinge Bracket:

Between 8.368 inches and 8.382 inches

Bottom Mounting Hole Diameter:

0.328 inches

Maximum Rated Armature Speed In Rpm:

7600

Thread Series:

Unf

Thread Class:

2a

Mounting Hole Thread Series Designator:

Unc

Mounting Hole Thread Diameter:

0.312 inches

Mounting Hole Thready Qty Per Inch (tpi):

18

Mounting Hole Thread Class:

2b

Thready Qty Per Inch (tpi):

20

Voltage In Volts:

6.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A14700