

View Online at <https://aerobasegroup.com/nsn/2920-00-640-7546>

Thread Direction:

Right-hand

Thread Length:

0.625 inches

Furnished Items:

Radio interference shielding

Second Step Diameter:

0.874 inches

Keyway Width:

0.250 inches

Unthreaded Portion Length:

1.688 inches

Mounting Hole Thread Direction:

Right-hand

Mounting Style:

Body mtd w/four threaded mtg holes

Environmental Protection:

Corrosion resistant and fungus resistant

Keyway Length:

1.000 inches

Submersibility:

Nonsubmersible

Shaft Rotation Direction:

Counterclockwise

Distance From End To Keyway Center:

1.250 inches

Thread Diameter:

0.625 inches

Armature Minimum Speed In Rpm At Full Current Output:

1330

Maximum Output Current Rating In Amps:

17.5

Minimum Current Cut-in Speed In Rpm:

1050

Shaft Drive End Style:

Straight shaft end, threaded, w/keyway

Distance From Raised Face To First Mounting Hole Center:

3.125 inches

Angular Deviation Of First Hole From Top Center In Deg:

135.0

Angular Deviation Of Second Hole From First Hole In Deg:

90.0

Distance From Raised Face To Second Mounting Center:

6.625 inches

Maximum Rated Armature Speed In Rpm:

4700

Thread Series:

Unf

Thread Class:

2a

Mounting Hole Thread Series Designator:

Unc

Mounting Hole Thread Diameter:

0.375 inches

Mounting Hole Thready Qty Per Inch (tpi):

16

Mounting Hole Thread Class:

2b

Thready Qty Per Inch (tpi):

18

Voltage In Volts:

28.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A14700