

View Online at <https://aerobasegroup.com/nsn/2920-00-640-7872>

Thread Direction:

Right-hand

Thread Length:

0.438 inches

Furnished Items:

Cooling fan and drive pulley and radio interference shielding

Second Step Diameter:

0.669 inches

Keyway Width:

0.125 inches

Unthreaded Portion Length:

0.781 inches

Mounting Hole Thread Direction:

Right-hand

Mounting Style:

Bracket mtd w/three mtg holes, top hole threaded

Environmental Protection:

Fungus resistant

Keyway Length:

0.625 inches

Submersibility:

Nonsubmersible

Shaft Rotation Direction:

Clockwise

Distance From End To Keyway Center:

0.781 inches

Thread Diameter:

0.669 inches

Armature Minimum Speed In Rpm At Full Current Output:

1800

Maximum Output Current Rating In Amps:

45.0

Minimum Current Cut-in Speed In Rpm:

1000

Grounding Method:

Internal

Shaft Drive End Style:

Straight shaft end, threaded, w/keyway

Distance Between Shaft Center And Bottom Mounting Hole Center:

3.375 inches

Distance Between Shaft Center And Top Mounting Hole Center:

3.188 inches

Angular Deviation Of First Hole From Top Center In Deg:

17.0

Angular Deviation Of Second Hole From First Hole In Deg:

163.0

Distance Between Inside Surfaces Of Hinge Bracket:

Between 6.680 inches and 6.694 inches

Distance Between Outside Surfaces Of Hinge Bracket:

Between 7.398 inches and 7.412 inches

Bottom Mounting Hole Diameter:

0.328 inches

Maximum Rated Armature Speed In Rpm:

8000

Thread Series:

Uns

Thread Class:

2a

Mounting Hole Thread Series Designator:

Unc

Mounting Hole Thread Diameter:

0.312 inches

Mounting Hole Thready Qty Per Inch (tpi):

18

Mounting Hole Thread Class:

2b

Thready Qty Per Inch (tpi):

20

Voltage In Volts:

6.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A14700