## NSN 2920-00-640-7873

Electrical Engine Starter Relay-solenoid - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2920-00-640-7873 **Mounting Hole Diameter:** 0.344 inches Submersibility: Nonsubmersible **Mounting Facility Spacing:** 1.750 in. C to c 68 degrees apart on 4.938 in. Bolt circle Voltage Rating: 32.0 volts **Hold-in Current:** 5.1 volt-ampere and 5.5 microwatts **Plunger Stroke Length:** 0.750 inches **Engaging Linkage:** Not included **Accommodated Linkage Threaded Hole Thread Size:** 3/8-20 **Contact Manual Closing Provision:** Not included **Control Terminal Quantity: Control Terminal Type:** Stud **Grounded Control Terminal:** Not included **Main Terminal Quantity:** 2 **Main Terminal Type: Control Terminal Quantity Internally Connected To Main Terminal:** Motor Diameter For Which Rigid Mount Is Designed: 4.938 inches **Mounting Facility Type And Quantity:** 4 hole **Special Features:** Special corrosion resistant treatment Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 2920-00-640-7873

Electrical Engine Starter Relay-solenoid - Page 2 of 2



Fiig:

T130-h