NSN 2920-00-640-7938

Electrical Engine Starter Relay-solenoid - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2920-00-640-7938 **Mounting Slot Width:** 0.281 inches **Mounting Slot Length:** 0.344 inches Submersibility: Nonsubmersible **Mounting Facility Spacing:** 1.750 in. C to c 66 degrees apart on 2.562 in. Radius Voltage Rating: 24.0 volts **Pull-in Current:** Between 34.7 amperes and 38.2 amperes **Hold-in Current:** 6.0 volt-ampere and 6.9 microwatts **Plunger Stroke Length:** 0.750 inches **Engaging Linkage:** Not included Accommodated Linkage Threaded Hole Thread Size: 1/4-20 **Contact Manual Closing Provision:** Not included **Control Terminal Quantity: Control Terminal Type:** Stud **Grounded Control Terminal:** Included **Main Terminal Quantity: Main Terminal Type:** Motor Diameter For Which Rigid Mount Is Designed: 5.125 inches **Mounting Facility Type And Quantity:** 4 slot **Special Features:** Fungus and corrosion resistant Shelf Life: N/a

Unit Of Measure:

NSN 2920-00-640-7938

Electrical Engine Starter Relay-solenoid - Page 2 of 2



em			

Yes - demil/mli

Fiig:

T130-h