

View Online at <https://aerobasegroup.com/nsn/2920-00-640-7938>

**Mounting Slot Width:**

0.281 inches

**Mounting Slot Length:**

0.344 inches

**Submersibility:**

Nonsubmersible

**Mounting Facility Spacing:**

1.750 in. C to c 66 degrees apart on 2.562 in. Radius

**Voltage Rating:**

24.0 volts

**Pull-in Current:**

Between 34.7 amperes and 38.2 amperes

**Hold-in Current:**

6.0 volt-ampere and 6.9 microwatts

**Plunger Stroke Length:**

0.750 inches

**Engaging Linkage:**

Not included

**Accommodated Linkage Threaded Hole Thread Size:**

1/4-20

**Contact Manual Closing Provision:**

Not included

**Control Terminal Quantity:**

2

**Control Terminal Type:**

Stud

**Grounded Control Terminal:**

Included

**Main Terminal Quantity:**

2

**Main Terminal Type:**

Stud

**Motor Diameter For Which Rigid Mount Is Designed:**

5.125 inches

**Mounting Facility Type And Quantity:**

4 slot

**Special Features:**

Fungus and corrosion resistant

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

T130-h