

View Online at <https://aerobasegroup.com/nsn/2920-00-659-7764>

**Body Material:**

Aluminum alloy

**Drive Connection Type:**

Impulse coupled

**Furnished Items:**

Booster coil

**Mounting Slot Width:**

0.406 inches

**Mounting Slot Length:**

0.750 inches

**Shaft Length:**

Between 0.505 inches and 0.509 inches

**Environmental Protection:**

Fungus resistant and submersible

**Distance Between Mounting Facility Centers:**

Between 4.184 inches and 4.192 inches

**Performance Type:**

High tension

**Drive Shaft Type:**

Tongue

**Shaft Rotation Direction:**

Counterclockwise

**Mounting Facility Quantity:**

1 and 1

**Pole Quantity:**

2

**Distributor Cap:**

Included

**Mounting Method:**

Flange

**Impulse Quantity Per Revolution:**

2

**Ignition Type For Which Designed:**

Single

**Secondary Terminal Type:**

Threaded

**Spark Plug Terminal Accommodation Thread Series:**

Unef

**Spark Advance Control Method:**

Manual

**Maximum Advance Deg:**

15.0

**Rotation Element Type:**

Permanent magnet rotor

**Contact Set Quantity:**

2

**Mounting Facility:**

Slot and threaded hole

**Features Provided:**

Radio interference shielding

**Spark Plug Terminal Accommodation Thread Diameter:**

Gap

**Spark Plug Terminal Accommodation Thread Diameter:**

0.688 inches

**Spark Plug Terminal Accommodation Thread Qty Per Inch (tpi):**

24

**Mounting Facility Thread Series:**

Unc

**Mounting Facility Thread Diameter:**

0.375 inches

**Mounting Facility Thread Qty Per Inch (tpi):**

16

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A12200