

View Online at <https://aerobasegroup.com/nsn/2920-00-659-7764>

Body Material:

Aluminum alloy

Drive Connection Type:

Impulse coupled

Furnished Items:

Booster coil

Mounting Slot Width:

0.406 inches

Mounting Slot Length:

0.750 inches

Shaft Length:

Between 0.505 inches and 0.509 inches

Environmental Protection:

Fungus resistant and submersible

Distance Between Mounting Facility Centers:

Between 4.184 inches and 4.192 inches

Performance Type:

High tension

Drive Shaft Type:

Tongue

Shaft Rotation Direction:

Counterclockwise

Mounting Facility Quantity:

1 and 1

Pole Quantity:

2

Distributor Cap:

Included

Mounting Method:

Flange

Impulse Quantity Per Revolution:

2

Ignition Type For Which Designed:

Single

Secondary Terminal Type:

Threaded

Spark Plug Terminal Accommodation Thread Series:

Unef

Spark Advance Control Method:

Manual

Maximum Advance Deg:

15.0

Rotation Element Type:

Permanent magnet rotor

Contact Set Quantity:

2

Mounting Facility:

Slot and threaded hole

Features Provided:

Radio interference shielding

Spark Plug Terminal Accommodation Thread Diameter:

Gap

Spark Plug Terminal Accommodation Thread Diameter:

0.688 inches

Spark Plug Terminal Accommodation Thread Qty Per Inch (tpi):

24

Mounting Facility Thread Series:

Unc

Mounting Facility Thread Diameter:

0.375 inches

Mounting Facility Thread Qty Per Inch (tpi):

16

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A12200