

View Online at <https://aerobasegroup.com/nsn/2920-00-674-6977>

Thread Direction:

Right-hand

Thread Length:

0.840 inches

Second Step Diameter:

0.875 inches

Unthreaded Portion Length:

Any acceptable

Mounting Hole Thread Direction:

Right-hand

Mounting Style:

Body mtd w/six threaded mtg holes

Pilot Height:

Any acceptable

Submersibility:

Nonsubmersible

Shaft Rotation Direction:

Clockwise

Thread Diameter:

0.625 inches

Ground Polarity Type:

Negative

Armature Minimum Speed In Rpm At Full Current Output:

1100

Grounding Method:

Internal or external

Shaft Drive End Style:

Straight shaft end, threaded

Distance From Raised Face To First Mounting Hole Center:

3.125 inches

Angular Deviation Of First Hole From Top Center In Deg:

38.0

Angular Deviation Of Second Hole From First Hole In Deg:

60.0

Distance From Raised Face To Second Mounting Center:

7.125 inches

Angular Deviation Of Third Hole From Second Hole In Deg:

164.0

Maximum Rated Armature Speed In Rpm:

2500

Thread Series:

Unf

Thread Class:

2a

Mounting Hole Thread Series Designator:

Unc

Mounting Hole Thread Diameter:

0.312 inches

Mounting Hole Thready Qty Per Inch (tpi):

18

Mounting Hole Thread Class:

2b

Thready Qty Per Inch (tpi):

18

Voltage In Volts:

12.0

Special Features:

Two additional mtg holes located 60 degrees from third row of holes

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A14700